

# Part 15 NPRM on Radar Detector Interference

**Hughes Network Systems** 

Paul Gaske, Robert Kepley, Joslyn Read

#### **HNS Overview**



HNS is the world's premier provider of broadband satellite services, products and network solutions

- Hughes Network Systems, a subsidiary of Hughes Electronics Corporation, is the world's largest provider of broadband satellite network solutions for businesses and consumers.
- Over 500,000 VSAT systems installed in more than 85 countries more than half of which are in the USA.
- HNS pioneered the development of high-speed satellite Internet access services, marketed globally under DirecPC® and DIRECWAY® brands.
- Revenues in 2001: \$1.3 billion.
- Headquartered in Germantown, MD, with a major facility in San Diego, CA, and more than 30 facilities and sales offices worldwide, HNS employs over 4,400 people in engineering, operations, marketing, sales, and support.
- HNS operates manufacturing facilities in Maryland; the U.K.; and Mexico.,

### Innovator of Broadband Services, Products, and Network Solutions



1983 1990 1994 1995







First Mesh VSAT (PES™)



**DIRECTV®** 



DirecPC®
Dial Return Service

1999 2000 2001 2003



DirecDuo™



Shipped 8,000,000th DIRECTV Set-Top box



DIRECWAY® Satellite Return Service



Next Generation K&band Broadband

#### **Corporate VSAT Services**



- VSATs provide networking services to every sector of the American economy:
  - Oil and gas
    - ◆ HNS has more than 40,000 gasoline retail locations under contract today
  - Financial services
  - Shipping
  - Merchandising
  - Telecommunications
  - Law enforcement
  - Local, state and federal governmental agencies
- VSAT services are provided today in C and Ku Bands under primary FSS allocation
  - VSATs operate pursuant to earth station licenses issued by the Commission
- Licensed operators and customers have legitimate expectation of protection from harmful interference

## **Current Regulation of Radar Detectors**



- Radar detectors as Part 15 devices are required to operate on a non-interference basis
- Radar detectors are exempted from emissions limits in Section 15.109 by Section 15.101(b)
  - Impractical and difficult to enforce existing part 15 noninterference rules against consumers who operate radar detectors
- General Section 15.109 Emissions Limit - but not Radar Detectors
  - 500 microvolts/meter measured at a distance of 3m for frequencies above 960 MHz
- FCC issued NPRM in October 2001 to resolve this radar detector interference problem and subject these devices to Part 15 emissions limits

## The Radar Detector Interference Problem



- Radar detectors produce harmful interference into licensed VSAT operations
  - Interference events increasing
  - New radar detectors active in more bands above 960 MHz
  - Levels emitted are <u>above</u> 100,000 microvolts/meter measured at a distance of 3 meters
- Commercial impact of this interference is significant
  - For Customers: Credit card and billing transactions may be rendered non-operational
  - For Satellite and Network Operators: Current and prospective customers are concerned about continued viability of VSAT services

### **Necessary Solution**



- Regulate emission levels of radar detectors
  - Need to establish emissions limit of <u>85 microvolts/</u> <u>meter measured at 3 meters</u> for radar detectors operating between 10.7-12.7 GHz
  - Subject radar detectors operating in other frequency ranges above 30 MHz to the relevant emission limits of 15.109(a)
- Require all radar detectors to comply with the new emission limits immediately
  - Apply new regulation to all radar detectors not yet sold
  - Impose compliance on radar detectors already in circulation through trade-in programs or other mechanisms

#### **Conclusion**



- Record is complete with uncontroverted showings of harmful interference caused to VSATs by radar detectors
- Need urgent action by FCC to establish rule for radar detectors with immediate effect
  - For radar detectors operating between 10.7-12.7 GHz,
    - Regulate emissions levels of radar detectors at level of 85 microvolts/meter measured at 3 meters
  - For radar detectors operating in other frequency ranges above 30 MHz,
    - Apply the relevant emissions limits of 15.109(a)
- Impose new regulation on all existing and future radar detectors